















## MATERIALS SPECIFICATIONS LINE

# GRANITOGRES RUSTICATO

### PRODUCT CHARACTERISTIC:

Supply of wear-resistant, stain-proof, frost proof, first grade, pressed, **unglazed** porcelain stoneware tiles **with chromatic effects obtained by full body colouring only**, fully vitrified in accordance with standards UNI EN 14411 ISO 13006– Group B1a UGL – with  $\leq 0.1\%$  water absorption. Obtained by selected mixtures of clay, quartz and feldspars fired at 1250°C, type **GRANITOGRES RUSTICATO** by **Casalgrande Padana**, with surface textures ..., formats ..., thickness ..., colour ..., series ..., chosen by the works management for the following places: ...

### TECHNICAL FEATURES:

  	NORM	ERGENISSE	
	Product classification	UNI EN ISO 14411	Group B1 UGL fully vitrified
	Dimensional and surface quality	UNI EN ISO 10545-2	Very low tolerance
	Water absorption	UNI EN ISO 10545-3	$\leq 0,10\%$
	Flexural strength	UNI EN ISO 10545-4	N/mm <sup>2</sup> 50-60
	Frost Resistance	All standards	Guaranteed
	Resistance to acids and alkalis with the exception of hydrofluoric acid	UNI EN ISO 10545-13	No damage
	Wear and abrasion resistance		Adequate for all purposes
	Linear thermal expansion	UNI EN ISO 10545-8	$6 \times 10^{-6}$
	Slip resistance (Matt surface)	DIN 51130	See every series
	Light fastness	DIN 51094	No change of colours
	Stain resistance		Guaranteed



Classement upec Surface naturelle Formats:  
de 10x20 à 30x30 cm.

CSTB

U<sub>4</sub>P<sub>4</sub>E<sub>3</sub>P<sub>2</sub>